# **PVC** handrail



GSP-1012-E/C



Rounded horizontal protections resistant to shocks and enhancing aesthetic. It can be set on one or tow heights in order to protect walls exposed to an intense traffic of trolleys in access areas or storage zones (hospitals, clinics, laboratories, elders' homes, clean rooms,...).

### **Characteristics**

#### Rounded bumper

• Height: 200 mm 7.9", 120 mm 4.7" or 60 mm 2.36"

Thickness: 30 mm 1.2"Length: 4 m 13.12'

• Material: antibacterial PVC classed M1 (Bs2d0), mass-coloured of thickness

3 mm 0.12"

• Surface aspect : smooth with some decorative grooves


• Fixation : by aluminium clip or in option on continuous aluminium rail


• Colours: 28 references for Impact 200 and 120 and 5 for Impact 60.


The finishing is guaranteed by end-pieces, external and internal angles at 90° in smooth PVC and aluminium connection pieces.

Fire class M1.

Its composition is heavy metals free and the thermal stabilization is made with calcium - zinc.









#### Installation

Middle part of the profile at 0,80 m 2.6' from the floor for a protection at half-height or above the skirtings for a protection in low part.

Installation thanks to aluminium clips set every 0,75 m 2.4' or in option on continuous aluminium rail.

## **PVC** handrail



GSP-1012-E/C

### Plates to be bonded "Contact"

Resistant and decorative, the "Contact" plate ensure a good protection of walls and doors exposed to scratches by furniture, beds, to rubs of chairs and to iterative shocks of trolleys (circulations, bedrooms and waiting rooms in public institutions). It also ensure the continuous with bumper "Impact".

Height: 200 or 350 mmThickness: 2,5 mmLength: 4 m


• Material: antibacterial PVC classified M1 (Bs2d0), tinted in the mass


• Surface aspect : smooth with some decorative grooves

• Fixation : plate equipped with foam-adhesive to reinforce with universal mastic glue

• Colours: 31 standards for "Contact 200" and 15 for "Contact 350".







## Bumper "Linéa' Punch Néo"

The bumper "Linea' Punch Neo" combines shocks resistance and design. It is made to fade into the background thanks to its refined profile, it can be easily associated with the handrail "Linea' Touch" to offer an aesthetic and efficient solution.

Height: 180 mmThickness: 25 mmLength: 4 m

• Material : antibacterial PVC classified M1 (Bs2d0), tinted in the mass of thickness

2,5 mm

• Surface aspect: matte central brushing

• Fixation : on aluminium clip or optional on aluminium rail

• Colours: 31 standards





